



Ford Motor Company of New Zealand Limited
Licensed Motor Vehicle Dealer
P.O. Box 30012, Lower Hutt

Bulletin

Service – Cars

GROUP 12 Bodywork No. 2

72-G-9

MODEL: XA Falcon/Fairlane

Page 1 of 1

Date : 24/5/72.

SUBJECT: (A) INTERIOR REAR VISION MOUNTING
(B) EXTERIOR REAR VIEW MIRROR.

A. The interior rear view mirror is retained to the windscreen glass with "loctite" adhesive, type 312NF which is available from B.R. Homersham Ltd. and distributors. The adhesive consists of two parts . An aerosol activator and the tube of adhesive. Should the rear vision mirror break away from the screen in service, the following replacement procedure should be adhered to:

1. Thoroughly clean the glass in the area where the mirror bracket is to be positioned.
2. Spray a thin coating of the activator onto the glass and leave until completely dry.
3. Clean the face side of the mirror bracket with abrasive cloth (80 grit), spray on a thin coating of activator and leave until completely dry.
4. Apply thin coating of adhesive to the face side of the mirror bracket and position immediately onto the glass. Hold the bracket in place for ten seconds.

B. The exterior rear view mirror housing is made from ABS plastic and painted exterior body colour to match the body. Should it be necessary to replace a mirror or to add a mirror to the left hand side of the vehicle, the following process should be adhered to when re-painting.

- 1, Wipe over with "dulon" thinners.
2. Apply two coats of "dulon" per the instructions on the tin. DO NOT apply the sealer coat as specified on the tin.


SERVICE DEPARTMENT.