

# RUBBER EDGE TRIM



EDGE TRIMS

Very Flexible to Fit Tight Radius

Pre-Applied Butyl Sealant or Hot-Melt Adhesive

**Rubber Edge Trims** are available in either **EPDM** or **Neoprene**, these two different materials are designed to fit your application perfectly.

**Neoprene** is a well proven proprietary blend that weathers well, has very good resistance to abrasion, flex cracking, alkalis, and acids and is best used in applications where flame resistance is a requirement. This material has moderate resistance to oils and gasoline. Neoprene is generally considered an excellent all-purpose material with a solid balance of properties and few limitations. However, expect poor resistance to aromatic and oxygenated solvents and limited flexibility at low temperatures. Hardness:70 Durometer (Shore A) Service temperature ranges from -40°F to 225°F.

**EPDM** has excellent performance characteristics. EPDM (Ethylene-Propylene-Diene-Monomer) is best known for its excellent ozone, weathering, and aging resistance. It also has excellent water and steam resistance, maintains its flexibility at low temperatures, features excellent resistance to alkalis, acids, and oxygenated solvents, and is very color stable. It is not recommended for resistance to oil, gasoline, and hydrocarbon solvents. EPDM is found in a wide range of applications and is excellent for use outdoors.

Hardness:70 Durometer (Shore A)  
Service temperature ranges from -40°F to 225°F.

**Butyl Sealant** can be ordered pre-applied and provides excellent sealing characteristic with good heat performance.

Service temperature ranges from -20°F to 158°F.

**Hot Melt Adhesive** can be ordered pre-applied and to provide a stronger grip with good heat performance.

Service temperature ranges from -20°F to 158°F.















**Cut to Length** All Rubber Edge Trims can be ordered in pre-cut lengths and can be individually packed. Minimum orders apply

## RUBBER EDGE TRIM-THICKNESS

1/32"	1/16"	1/16"	1/8"
0.032	0.063	0.063	0.125
 X1001	 X1002	 X2017	 X1003
 X1010	 X1011		 X1012
 X2001	 X2002	 X2073	 X2003
 X2012	 X2013	 X2008	 X2014
 X2059	 X2010		 X2102
 X1466	 X2009		 X2006

# RUBBER EDGE TRIM

EDGE TRIMS

3/16"	1/4"	5/16"	3/8"
0.188	0.250	0.313	0.375
 <p>X1004</p>	 <p>X1005</p>	 <p>X1006</p>	 <p>X1007</p>
 <p>X1013</p>	 <p>X1014</p>	 <p>X1015</p>	 <p>X1016</p>
 <p>X2004</p>	1/8	1/2"	3/4"
	0.125	0.500	0.750
 <p>X2015</p>	 <p>X2060</p>	 <p>X1018</p>	 <p>X2007</p>
	 <p>X2011</p>		

## HOW TO ORDER

**Neoprene Part# Example**

X1001 WG

WG=with glue  
WB=with pre-applied butyl sealant

Rubber Edge Trim profile

**EPDM Part# Example**

X1001 E WG

WG=with glue  
WB=with pre-applied butyl sealant

E=EPDM

Rubber Edge Trim profile